

# ELEGANCE 4084

## Electronic ICU and Patient Bed, 4 Motors



4 motors

Electronic adjustments of backrest, footrest, height

Trendelenburg and Reverse Trendelenburg functions

Fowler, Vascular and Cardiac positions

Auto-contour

- Hand control unit

Water-proof nurse control panel at foot-end

Single button adjustments of Trendelenburg, Cardiac, Examination,  
Vascular, Patient Evacuation functions

Aluminum & HPL side rails easily cleanable, lockable and fold-away

Aluminum & HPL detachable foot and head boards

Auto-regression system

Auto-CPR button

4 section, detachable ABS mattress platform

ABS covered sub-frame

Electrostatic powder coated metal frame

Gradually adjustable footrest

Drainage bag hooks at both sides

Protective plastic corner bumpers

Height adjustable stainless steel IV pole

Central lockable castors

IV pole sockets located at all four corners.

### Optional Accessories:

Battery back - up

Bed extension

Manual CPR at backrest

Oxygen tube holder

File holder

Foam Mattress

Lifting pole

Monitor tray at foot -end

X-ray cassette holder at backrest

Linen holder

# ELEGANCE 4084



Electronic ICU and Patient Bed, 4 Motors



*Multifunctional & Waterproof Nurse Control Panel*



*Hand Control Unit*



*Aluminum & HPL Design Lockable Fold-Away Side Rails*



*Central Lockable Castors*

## TECHNICAL DETAILS

|                              |                                      |
|------------------------------|--------------------------------------|
| External Dimensions:         | 101x235cm                            |
| Mattress Platform:           | 85x195cm                             |
| Height (without mattress):   | 46-86cm                              |
| Backrest Angle:              | 0°-70°                               |
| Footrest Angle:              | 0°-42°                               |
| Trendelenburg Angle:         | 0°-14°                               |
| Reverse Trendelenburg Angle: | 0°-14°                               |
| Castor Diameter:             | 150mm                                |
| Safe Working Load Capacity:  | 250 kg                               |
| <b>ELECTRICAL DATA</b>       |                                      |
| Power Input                  | max. 3,15A<br>100V – 240V ~ 50/60 Hz |
| Electrical Shock Protection  | Class I, Type B                      |
| Liquid ingress protection    | IPx66                                |